

SUITABLE FOR SINGLE SWING GATES UP TO 2.5 METRES









RESIDENTIAL SWING GATE OPENER

KEY FEATURES

SUITABLE FOR SWING GATESSuited for Single Swing Gates up to 2.5 metres

MYQ CAPABLE

Opener is myQ capable for gates with an additional purchase of Safety IR Beams & myQ Gateway.¹


BATTERY BACKUP COMPATIBLE

Opener is Battery Backup compatible with additional purchase of Battery Backup accessory.²



Compliant to Australian and New Zealand Standard AS/NZS 60335.2.103

SMART





SOFT-START AND SOFT-STOP for smooth operation.

SPEED ADJUSTMENT allows you to increase and decrease opening and closing gate speeds.

PEDESTRIAN MODE allows for customised gate opening access.

QUIET & RELIABLE

240V MAINS VOLTAGE

3-YEAR WARRANTY

P44 WEATHER RESISTANT ingress protection IP44 suitable for outdoor installation.

QUIET DC MOTOR eliminates noise and vibrations, providing smooth operation.

BATTERY BACKUP ensures access even when the power is out.²

120° WIDE OPENING ANGLE

SINGLE SWING GATES UP TO 2.5 METRES

SAFE & SECURE

m

SECURITY+ 2.0° sends a new code with every remote click.

PREMIUM AUTOMATIC SAFETY REVERSE function will allow your gate to stop and reverse automatically if obstructed in opening or closing.

TIMER-TO-CLOSE automatically closes the gate after a pre-set amount of time.3

((*)) IMPROVED TRANSMITTER RANGE has up to 18% better range meaning you can start opening your gate sooner.

AUTOMATIC FORCE SENSING monitors and adjusts the force needed to open your gate with each operation.

DISENGAGEMENT MECHANISM allows you to manually open the gate whenever needed.

ACCESSORIES INCLUDED



FOUR BUTTON REMOTE CONTROLS

Premium remotes to control up to 4 garage doors or gates. Each button can be programmed to Security+ and Security+ 2.0 devices.

POWERFUL ADD-ONS

E970M

M828AU772



GATE MYQ CONNECTIVITY BUNDLE

Add monitoring and control away from home. Includes myQ Gateway and The Outdoor Protector System (Safety IR Beams).



BATTERY BACKUP

Get in and out when the power's out with Battery Backup. Batteries fit within the housing of the opener.



WIRELESS SECURITY KEYPAD

Convenient and safe access to open and close your gate without using a remote control or key.



E-LOCK Additional security with electric lock.



MAG-LOCK Additional security with magnetic lock.



SWING GATE STOP Additional security with centre drive gate stop.



SWING GATE STOP Additional security with bolted down gate stop.

FOUR BUTTON CAR VISOR REMOTE CONTROL

Easily attaches to your car visor to control up to 4 garage doors or gates. Can be programmed to Security+ and Security+ 2.0 devices.

gomerlin.com.au gomerlin.co.nz

¹ Additional purchase of Merlin myQ Gateway and Safety IR Beams accessories required to enable myQ functionality. Visit gomerlin.com.au or gomerlin.com.z for further information.² Additional purchase of Merlin Battery Backup functionality. Visit gomerlin.com.au or gomerlin.com.z for further information ¹ Safety IR Beams must be installed to enable the use of Timer-to-Close. See User Guide for additional information.⁴ When compared to other available products.











RESIDENTIAL SWING GATE OPENER

Start with smart. Compatible with myQ²

Additional purchase of The Outdoor Protector System and myQ Gateway is required

FOR SWING GATES

- · Monitor and control your gate away from home through the myQ App.
- · Peace of mind knowing if gate is open or closed anywhere and any time.
- Receive real time alerts and notifications so you know when the gate is opened or closed by loved ones.

APP AVAILABLE ON-








- · See history records of your gate open and close periods.
- · Protect your loved ones and belongings with The Outdoor Protector System (Safety IR Beams).
- · Compatible myQ App available for smart devices including Apple Watch.

TYPICAL INSTALLATION - SINGLE SWING GATES



- 1. Gate Opener (MGA)
- 2. Remote Control (E970M)

Maximum Gate Width & Weights:

- 200kg for 1.5m gate
- · 150kg for 2m gate
- · 100kg for 2.5m gate

SECURITY+ 2.0°

- · Encrypted rolling code across multiple frequencies.
- · Security+ 2.0® technology virtually eliminates interference.



RADIO

- · Provides 2-way communication from gate openers and accessories.
- · Receiver with 64 memory register.





GATE TRAVEL SPEED

· Opens 120° in 13-15 Seconds.

STANDARD SPECIFICATIONS

- · Main AC Supply: 220-240Vac; 50/60Hz
- · Motor Voltage: 24 VDC
- · Input Power: 100 W
- · Ambient Temperature Range: -20-+55*C
- · Max peak pulling force: 200 Nm
- · Radio frequency: 433.30, 433.92, 434.54 MHz with Security+ 2.0 technology
- · Compatible with myQ Technology2
- · Gate Opener Capacity of up to 64 memory registers





AUSTRALIA

Chamberlain Australia Ptv Ltd PO Box 1446 Lane Cove NSW 1595 Australia

gomerlin.com.au 1800 638 234

NEW ZEALAND

Chamberlain New Zealand Ltd PO Box 100-221 North Shore Auckland 0745 New 7ealand

gomerlin.co.nz 0800 653 667

Engineered and designed by The Chamberlain Group, Inc. ©2021 The Chamberlain Group, Inc.™ Trademark of The Chamberlain Group, Inc. • Registered Trademark of The Chamberlain Group, Inc.



¹This feature requires monitored Safety IR Beams to be fitted. Linking your myQ account to partner may require an additional accessory purchase or subscription fee. Apple, the Apple logo, iPhone, and iPad are trademarks of Apple Inc., registered in the U.S. and other countries and regions. App Store is a service mark of Apple Inc. Google Play and the Google Play logo are trademarks of Google LLC. Smartphone not included.